

BIND



BIND IS A PENETRATING PRIMER WITH A HIGH QUALITY ACRYLIC WATER BOND AND LOW VISCOSITY. IT WORKS ON ALL SURFACES AS IT PROVIDES EXCELLENT ADHESION WITH DIFFERENT MATERIALS. IT IS ALSO HIGHLY FLEXIBLE AND IMPACT RESISTANT.

USES

BIND can be applied to new and old concrete, bricks, asbestos, plaster, slates, hard boards, aluminum, chip boards, roof tiles, pre painted areas, steel etc.

ADVANTAGES

- deep penetration and excellent permeability
- resistant to corrosion, heating, high fire and UV
- it does not chip or scale easily
- produces no toxic substances.
- is odourless
- has excellent adhesion
- is waterproof

APPLICATION

Eliminate any fat deposits, grease, oil, laitance and other chemical substances present on the surface. Leave concrete for a minimum of 28 days before applying. Make sure there is no loose adhesion or flaking metal before applying to old weathered surfaces. Clean the area by hosing or washing with water before applying SELFCOAT BIND.

TECHNICAL PROPERTIES

Colour	Wet - Creamy. Dry - Transparent
UV resistance	Excellent
Chemical resistance	Excellent
Water resistance	Excellent
Hardening resistance	Excellent
Drying time	30min (touch dry) 24 Hours (full cure)
Spreading rate	12-18 m ²

CLEANUP

Use water to clean all the equipment thoroughly after using it.

STORAGE

Store the sealed containers at moderate temperatures.

order online at www.ecopaint.co.za

call: 082 580 9935

email: info@ecopaint.co.za

web: www.ecopaint.co.za