

WOOD SEALANT



WOOD SEALANT HAS EXCELLENT SEALING FEATURES AS IT IS A WATER BOND ACRYLIC, ELECTROMETRIC MEMBRANE MADE INTO A CLEAR PRODUCT. IT ACTS ON THE GREASE, OIL, ALKALIS AND ACIDS THAT LEAD TO DESTRUCTION OF THE MATERIAL BY SEEPING DEEP IN TO ITS SURFACE. THE RESIN HELPS TO MEND MINOR AND HAIRLINE CRACKS. IT ACTS AS A WATERPROOF SURFACE AND KEEPS OUT DUST AS WELL. CHEMICAL AND ABRASION RESISTANT ARE SOME OTHER QUALITIES OF VARNISHES.

USES

WOOD SEALANT protects the natural color of surfaces such as wooden doors, roof tiles, wooden doors, stones and bricks, it is perfect as a waterproof coat. It is even used to strengthen fiberglass to optimize its use.

ADVANTAGES

- ultraviolet, heat and stain resistant
- no discolouration with age
- good adhesion and flexibility
- excellent efflorescence protection

APPLICATION

Get rid of the chemical and fat deposits, oil and laitance from the surface. Leave concrete prior to 28 days of application. Wash the older surfaces with sandblasting or pressure jet as convenient. A damp cloth should be used to wipe the wooden areas. Varnish the wooden surfaces and sand them after removing everything. Appropriate weather conditions are a must while applying varnish. Sheen will appear if there is a constant water flow on the area being applied with varnish. Sheen will go away after a drying period.

TECHNICAL PROPERTIES

Colour	Available as a clear product or stains such as Ebony, Oak, Mahogany or matched as required.
UV resistance	Excellent
Chemical resistance	Excellent
Water resistance	Excellent
Hardening resistance	Excellent
Drying time	24 Hours (full cure)
Spreading rate	10-15 m ² /L (depending on substrate)

CLEANUP

Use water to clean all the equipment thoroughly after using it.

STORAGE

Store the sealed containers at moderate temperatures.

order online at www.ecopaint.co.za

call: 082 580 9935

email: info@ecopaint.co.za

web: www.ecopaint.co.za